

IC 022 EVO, IC 022 EVO PLUS

Discover a new dimension in surface cleaning with our revolutionary two - hose dry ice blasting system



Standard dry ice pellets
1.5 mm / 3 mm



Low air consumption
0,3 - 1,1 m³/min



Lightweight
19 kg



Low noise
65 - 85 dB (A)



Added benefit
Maintenance free design

ERGONOMIC BLAST GUN WITH LED LIGHT

2 NOZZLES (ROUND & FLAT)

STANDARD AIR HOSE COUPLING

3 m BLAST HOSE

TROLLEY WITH STORAGE BOX

DRY ICE BOX 25 KG



PRESSURE VALVE ON GUN



EASY - TO - OPERATE



ACCESSORIES




Development



Manufacturing



Maintenance and Repair



Training

Characteristics

Discover a new generation of feeding systems bring additional 20% power.

Dry ice cleaning is now also available to car workshops, car dealerships, all manufacturing or maintenance companies in any industry, big or small. We bring you a cost-effective alternative to traditional cleaning methods.

The unique design of the IC 022 EVO offers surprising flexibility, performance and power. The maintenance-free feeding system from ICS accepts both 1,5 mm and standard 3 mm dry ice pellets.

The excellent design of the blaster allows easy handling even in tight access spaces. The operation of the machine is easy and fast to get used to.

With IC 022 EVO you are equipped to manage very wide variety of cleaning tasks.

IC 022 EVO with its unique feeding system offers unrivalled performance at an unbeatable price.

Technical specifications

<ul style="list-style-type: none">■ Dimensions Length: 528 mm Width: 296 mm Height: 336 mm	<ul style="list-style-type: none">■ Consumption Dry ice: up to 25 kg/h Compressed air: 0.3 – 1,1 m³/min. depending on the nozzle type	<ul style="list-style-type: none">■ Input Pressure 4 - 10 bar
<ul style="list-style-type: none">■ Weight Empty machine: 19 kg with the hose	<ul style="list-style-type: none">■ Hopper capacity 4 kg	<ul style="list-style-type: none">■ Operating pressure 2 - 8 bar
<ul style="list-style-type: none">■ Material Casing: Fibreglass Wheel frame: Stainless steel	<ul style="list-style-type: none">■ Noise level 65 – 85 dB (A) depending on the blasting pressure and the cleaned surface	<ul style="list-style-type: none">■ Compressed air supply: NW 7.2 coupling, acc. ISO 4414/EN 983 standard Minimum requirements for compressed air according to ISO 8573-1:2010 [1:4:1]

IC 022 EVO



IC 022 EVO PLUS



Standard package contents

- **10 m Air Hose**
With quick connect fitting
- **Protective Equipment Kit**
Protective suit, Gloves, Goggles, Ear plugs, Respirator
- **Round nozzle**
RN - 22 - 08 - 000
- **Dry Ice Shovel**
1 kg Capacity plastic shovel
- **Flat Nozzle with Adapter**
FN-20-10-200, NA-20-10-001

PLUS Accesories

- **Trolley**
- **Ice Box**




Development



Manufacturing



Maintenance and Repair



Training